

Product datasheet

Chipboard screw (TURBO) (PH) for wood stud

V/S/B



Function: Sharp tip and threads adapted for anchoring in wood. The threads immediately grip and tighten the screw to the chipboard, while the grooves underneath the head sink the screw. The unique tightening features of the screw have been achieved by providing the screw with a cutting drill tip, as well as with oblique and longitudinal flanks between the threads. This provides the following benefits:

- Less risk of cracks in wood.
- Lower torque when tightening.
- Less screwing time.

Track type bit: Philips 2.



Material: Case hardened steel.

Coating: Zinc-plated 5 my, for indoor use.

Installation instructions: A power screwdriver with depth stop, speed of 2,000-3,000 rpm is recommended.

Sizing: About 20 pcs/m², screw spacing 20 cm.

TURBO
SPÅNSKRUV®



D	L	G	Art.no	Quantity	Pack.	MB
4.2	51	29	T8051	3500	Bulk pack	
4.2	51	29	T8151	500	Packaging	8
4.2	51	29	T8951	200	Packaging	12
4.8	75	45	T8075	2000	Bulk pack	
4.8	75	45	T8175	250	Packaging	8
4.8	75	45	T8975	100	Packaging	16

NOTE: Packs are only sold in multiples of ten.



Produkten bedömd i
SundaHus Miljödata

EPD®
THE INTERNATIONAL EPD® SYSTEM

