Product datasheet


Chipboard screw (TURBO) (TX) for wood stud



TURBO

SPÅNSKRUV'









Function: Sharp tip and threads adapted for anchoring in wood. The threads immediately grip and tighten the screw to the chipboard, while the grooves underneath the head sink the screw. Suitable for assembly of chipboard, OSB, Plywood and other wood-based boards. The unique tightening features of the screw have been achieved by providing the screw with a cutting drill tip, as well as with oblique and longitudinal flanks between the threads. This provides the following benefits:



- · Lower torque when tightening.
- · Less screwing time.

Track type bit: TX 20.

Material: Case hardened steel.

Coating: Zinc-plated 5 my, for indoor use.

Installation instructions: A power screwdriver with depth stop, speed of 2,000-3,000 rpm is recommended.

Sizing: About 20 pcs/m², screw spacing 20 cm.

| D | L | G | Art.no | E-number | Quantity | Pack. | МВ |
|-----|----|----|--------|----------|----------|-----------|----|
| 4.2 | 30 | 19 | T9030 | | 8000 | Bulk pack | |
| 4.2 | 30 | 19 | AT9130 | | 3000 | Large box | |
| 4.2 | 30 | 19 | T9130 | | 1000 | Packaging | 8 |
| 4.2 | 30 | 19 | T9930 | | 250 | Packaging | 16 |
| 4.2 | 41 | 21 | T9041 | | 5000 | Bulk pack | |
| 4.2 | 41 | 21 | AT9141 | | 1800 | Large box | |
| 4.2 | 41 | 21 | T9141 | | 600 | Packaging | 8 |
| 4.2 | 41 | 21 | T9941 | | 200 | Packaging | 16 |
| 4.2 | 57 | 35 | T9057 | | 3500 | Bulk pack | |
| 4.2 | 57 | 35 | AT9157 | | 1200 | Large box | |
| 4.2 | 57 | 35 | T9157 | | 500 | Packaging | 8 |
| 4.2 | 57 | 35 | T9957 | | 150 | Packaging | 16 |
| 4.8 | 75 | 45 | T9075 | | 2000 | Bulk pack | |
| 4.8 | 75 | 45 | T9175 | | 250 | Packaging | 8 |
| 4.8 | 75 | 45 | T9975 | | 100 | Packaging | 16 |
| | | | 1/1 | | | | |

NOTE: Packs are only sold in multiples of ten.



