Product datasheet

Chipboard screw (TURBO) (TX) for wood stud

V/S/B



Function: Sharp tip and threads adapted for anchoring in wood. The threads immediately grip and tighten the screw to the chipboard, while the grooves underneath the head sink the screw. Suitable for assembly of chipboard, OSB, Plywood and other wood-based boards. The unique tightening features of the screw have been achieved by providing the screw with a cutting drill tip, as well as with oblique and longitudinal flanks between the threads. This provides the following benefits:

- Less risk of cracks in wood.
- Lower torque when tightening.
- Less screwing time.

Track type bit: TX 20.

Material: Case hardened steel.

Coating: Zinc-plated 5 my, for indoor use.

Installation instructions: A power screwdriver with depth stop, speed of 2,000-3,000 rpm is recommended.

Sizing: About 20 pcs/m^2, screw spacing 20 cm.

D	L	G	Art.no	Quantity	Pack.	MB
4.2	30	19	T9030	8000	Bulk pack	
4.2	30	19	AT9130	3000	Large box	
4.2	30	19	T9130	1000	Packaging	8
4.2	30	19	T9930	250	Packaging	16
4.2	41	21	T9041	5000	Bulk pack	
4.2	41	21	AT9141	1800	Large box	
4.2	41	21	T9141	600	Packaging	8
4.2	41	21	T9941	200	Packaging	16
4.2	57	35	T9057	3500	Bulk pack	
4.2	57	35	AT9157	1200	Large box	
4.2	57	35	T9157	500	Packaging	8
4.2	57	35	T9957	150	Packaging	16
4.8	75	45	T9075	2000	Bulk pack	
4.8	75	45	T9175	250	Packaging	8
4.8	75	45	T9975	100	Packaging	16

NOTE: Packs are only sold in multiples of ten.

CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden