

Product datasheet

Decking screw (A2 stainless steel) for wood stud

V/S/B[®]
VÄSTSVENSK BYGGSKRUV AB



Function: Sharp tip and threads adapted for anchoring in wood. The threads immediately grip and tighten the screw to the decking, while the grooves underneath the head sink the screw. Suitable for installing decking, balconies, fences etc. The unique tightening features of the screw have been achieved by providing the screw with a cutting drill tip, as well as with oblique and longitudinal intersections between the threads. This provides the following benefits:

- Less risk of cracks in wood.
- Lower torque when tightening.
- Less screwing time.


Track type bit: TX 20.

Material: Stainless steel (A2).

Installation instructions: A power screwdriver with a depth stop is recommended, recessed head approximately 2 mm.

Sizing: About 30 pcs/m².

TURBO
TRALLSKRUV[®]



Produkten bedömd i
SundaHus Miljödata



D	L	G	Max comp. thick. app. mm	Art.no	E-number	Quantity	Pack.	MB
4.2	35	22		B635		8000	Bulk pack	
4.2	35	22		635		250	Packaging	16
4.2	41	22	22	B641		5000	Bulk pack	
4.2	41	22	22	6419		600	Packaging	8
4.2	41	22	22	64100		200	Packaging	16
4.2	57	26	28	B657		3500	Bulk pack	
4.2	57	26	28	6579		300	Packaging	8
4.2	57	26	28	65700		150	Packaging	12
4.8	75	35	34	B675		2000	Bulk pack	
4.8	75	35	34	675		250	Packaging	8
4.8	75	35	34	67500		100	Packaging	16
4.8	100	60		B6100		2000	Bulk pack	
4.8	100	60		6100		100	Packaging	12

CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden

