

Product datasheet

Decking screw cylindrical (external) for wood stud

V/S/B[®]
VÄSTSVENSK BYGGSKRUV AB



Function: Sharp tip and threads adapted for anchoring in wood. The threads immediately grip and tighten the screw to the decking. The threads underneath the head fix the decking while the head sinks by itself. Suitable for installing decking, balconies, fences etc. The unique tightening features of the screw have been achieved by providing the screw with a cutting drill tip, as well as with oblique and longitudinal flanks between the threads. This provides the following benefits:

- Less risk of cracks in wood.
- Lower torque when tightening.
- Less screwing time.

Drive type: TX 20.

Material: Case hardened steel.

Surface treatment: Zincotech Au, corrosivity class C4, for outdoor use.

Installation instruction: A power screwdriver with depth stop is recommended, countersunk head approximately 2 mm.

Dimension: About 30 pcs/m².



Produkten bedömd i
SundaHus Miljödata



| D | L | G | Max comp. thick. app. mm | Art.no | Quantity | Pack. | MB |
|-----|----|----|--------------------------|---------|----------|-------------|----|
| 4.8 | 60 | 27 | 28 | B9557 | 2500 | Bulk pack | |
| 4.8 | 60 | 27 | 28 | 9557 | 350 | Packaging | 8 |
| 4.8 | 60 | 27 | 28 | P9557 | 300 | Plastic box | 8 |
| 4.8 | 60 | 27 | 28 | P955700 | 150 | Plastic box | 12 |
| 4.8 | 60 | 27 | 28 | 955700 | 150 | Packaging | 16 |
| 4.8 | 75 | 34 | 34 | B9575 | 1500 | Bulk pack | |
| 4.8 | 75 | 34 | 34 | 9575 | 250 | Packaging | 8 |
| 4.8 | 75 | 34 | 34 | P9575 | 200 | Plastic box | 8 |
| 4.8 | 75 | 34 | 34 | 957500 | 100 | Packaging | 16 |
| 4.8 | 75 | 34 | 34 | P957500 | 100 | Plastic box | 12 |

CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden

