

Product datasheet

Collated drywall screw for steel plate max

1 mm

V/S/B
VÄSTSVENSK BYGGSKRUV AB



Function: Straight tip with double thread grooves that grip immediately, penetrate the steel plate very quickly and sink into the drywall board without damaging the cardboard layer.

V/S/B
VÄSTSVENSK BYGGSKRUV AB

Track type bit: Philips 2.

Material: Case hardened steel.

Coating: ZP = Zinc-plated 5 my, PHO = phosphated, for indoor use.

Installation instructions: A power screwdriver with a speed of 2,000-5,000 rpm is recommended.

Sizing: Around 15 pcs/m², screw spacing 20 cm on the edge of the sheet and 30 cm on the inner section.



D	L	Surface treat.	G	Art.no	E-number	Quantity	Pack.	MB
3.5	25	PHO	20	RBF2025		1000	Packaging	6
3.5	25	ZP	20	RB2025		1000	Packaging	10
3.5	38	PHO	33	RBF2038		1000	Packaging	10
3.5	38	ZP	33	RB2038		1000	Packaging	10
3.5	41	PHO	36	RBF2041		1000	Packaging	10
3.5	51	PHO	46	RBF2051		1000	Packaging	6
3.5	51	ZP	46	RB2051		1000	Packaging	8



CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden

