



**Function:** Drill tip with diameter adapted to suit sheet metal, drills very quickly in sheet metal up to 2 x 1.25 mm. Wood thread provides solid anchoring in timber. EPDM rubber for watertight seal. The head's low-profile pan design fits superbly to most external façade panels as well as other external attachments.





**Track type bit:** TX 20.

**Material:** Case hardened steel and EPDM rubber.

**Coating:** Zinc-plated 20 my. Powder coated with polyester lacquer, for outdoor use.

**Installation instructions:** A power screwdriver with a speed of 1,500-2,500 rpm is recommended.

**Sizing:** About 6-8 pcs/m<sup>2</sup>.



D	L	Colour	Art.no	E-number	Quantity	Pack.	MB
4.8	35	Black RAL 9005	P683422		100	Plastic box	12
4.8	35	Black RAL 9005	683422		100	Packaging	12
4.8	35	Black RAL 9005	SB683422		10	Pack	10
4.8	35	Brick red RAL 8004	683433		100	Packaging	12
4.8	35	Brick red RAL 8004	SB683433		10	Pack	10
4.8	35	Dark red RAL 3009	683455		100	Packaging	12
4.8	35	Dark red RAL 3009	SB683455		10	Pack	10
4.8	35	Silver RAL 9006	683477		100	Packaging	12
4.8	35	Silver RAL 9006	SB683477		10	Pack	10
4.8	35	White RAL 9010	P683444		100	Plastic box	12
4.8	35	White RAL 9010	683444		100	Packaging	12
4.8	35	White RAL 9010	SB683444		10	Pack	10

NOTE: Packs are only sold in multiples of ten.

