

# Product datasheet

Façade overlap screw (external) for sheet metal max 2 x 1,25 mm

**V/S/B**  
VÄSTSVENSK BYGGSKRUV AB



**Function:** Drill tip for sheet metal up to 2 x 1.25 mm. Sheet metal thread for overlap function. EPDM rubber for watertight seal. The head's low-profile pan design works superbly when attaching sheet metal to sheet metal externally.

**V/S/B**  
VÄSTSVENSK BYGGSKRUV AB

**Track type bit:** TX 20.

**Material:** Case hardened steel and EPDM rubber.

**Coating:** Zinc-plated 20 my. Powder coated with polyester lacquer, for outdoor use.

**Installation instructions:** A power screwdriver with a speed of 1,500-2,500 rpm is recommended.



D	L	Colour	Art.no	E-number	Quantity	Pack.	MB
4.8	23	Black RAL 9005	P683222		100	Plastic box	16
4.8	23	Black RAL 9005	683222		100	Packaging	16
4.8	23	Black RAL 9005	SB683222		10	Pack	10
4.8	23	Brick red RAL 8004	683233		100	Packaging	16
4.8	23	Brick red RAL 8004	SB683233		10	Pack	10
4.8	23	Dark red RAL 3009	683255		100	Packaging	16
4.8	23	Dark red RAL 3009	SB683255		10	Pack	10
4.8	23	Silver RAL 9006	683277		100	Packaging	16
4.8	23	Silver RAL 9006	SB683277		10	Pack	10
4.8	23	White RAL 9010	P683244		100	Plastic box	16
4.8	23	White RAL 9010	683244		100	Packaging	16
4.8	23	White RAL 9010	SB683244		10	Pack	10

NOTE: Packs are only sold in multiples of ten.



## CUSTOMER SERVICE

Tel. 033-23 03 03  
Email: vsb@vsbyggskruv.se  
Website: vsbyggskruv.se

## ADDRESS

Västsvensk Byggskruv AB  
Vävlagargatan 7  
507 30 Brämhult  
Sweden

