

Product datasheet

Barge board screw (external) for sheet metal max 2 x 1,25

mm

V/S/B[®]
VÄSTSVENSK BYGGSKRUV AB



Function: Drill tip with diameter adapted to suit sheet metal, drills very quickly in sheet metal up to 2 x 1.25 mm. Wood thread provides solid anchoring in timber. The screw is designed for mounting of sheet metal (water board) to wind boards and other external mounting. Sealing washer for safe tightening.

Drive type: TX 20.

Material: Case hardened steel and EPDM rubber.

Surface treatment: Zytac™ +. Powder coated with polyester lacquer, for outdoor use.

Installation instruction: A power screwdriver with a speed of 1,500- 2,500 rpm is recommended.



D	L	Colour	Art.no	Quantity	Pack.	MB
4.2	25	Black RAL 9005	P684822	200	Plastic box	16
4.2	25	Black RAL 9005	684822	200	Packaging	16
4.2	25	Black RAL 9005	SB684822	10	Pack	10
4.2	25	Brick red RAL 8004	684833	200	Packaging	16
4.2	25	Brick red RAL 8004	SB684833	10	Pack	10
4.2	25	Dark red RAL 3009	684855	200	Packaging	16
4.2	25	Dark red RAL 3009	SB684855	10	Pack	10
4.2	25	Silver RAL 9006	684877	200	Packaging	16
4.2	25	Silver RAL 9006	SB684877	10	Pack	10
4.2	25	White RAL 9010	P684844	200	Plastic box	16
4.2	25	White RAL 9010	684844	200	Packaging	16
4.2	25	White RAL 9010	SB684844	10	Pack	10



CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden

