

Product datasheet

Farmer screw (aluminium) for wood stud

V/S/B
VÄSTSVENSK BYGGSKRUV AB



Function: Drill tip with diameter adapted to suit aluminium sheet, drills very quickly in aluminium sheet up to 2 x 1.25 mm. Wood thread provides solid anchoring in timber. Hexagon head with flange for safe tightening. Sealing washer for secure seal.

V/S/B
VÄSTSVENSK BYGGSKRUV AB

Track type bit: Clamping sleeve 8 mm.

Material: Aluminium and aluminium washer with vulcanised EPDM rubber.

Installation instructions: A power screwdriver with a speed of 1,500-2,500 rpm is recommended.

Sizing: About 6-8 pcs/m².



D	L	Colour	Art.no	E-number	Quantity	Pack.	MB
5.5	35	Black RAL 9005	485029		150	Packaging	8
5.5	35	Brick red RAL 8004	485039		150	Packaging	8
5.5	35	Dark red RAL 3009	485059		150	Packaging	8
5.5	35	Uncoloured	485019		150	Packaging	8
5.5	35	White RAL 9010	485049		150	Packaging	8



CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden

