

# Product datasheet

Building sheet screw (A2 stainless steel/bi metal) for beams max 12,5 mm

**V/S/B**<sup>®</sup>  
VÄSTSVENSK BYGGSKRUV AB

**Function:** Drill tip with diameter adapted to suit sheet metal, drills in beams up to 12.5 mm. Hexagon head with flange and sealing washer for safe tightening.

**Drive type:** Clamping sleeve 8 mm.

**Material:** Stainless steel (A2) with welded drill tip in case hardened steel and stainless steel washer with vulcanised EPDM rubber.

**Installation instruction:** A power screwdriver with a speed of 1,500-2,500 rpm is recommended.



D	L	Min drill cap. mm	Max drill cap. mm	Art.no	Quantity	Pack.	MB
4.8	20	1.3	4	48121	250	Packaging	8
5.5	25	1.3	3.5	48122	250	Packaging	8
5.5	26	2	6	48123	250	Packaging	8
5.5	40	4	12.5	481249	150	Packaging	8



## CUSTOMER SERVICE

Tel. 033-23 03 03  
Email: [vsb@vsbyggskruv.se](mailto:vsb@vsbyggskruv.se)  
Website: [vsbyggskruv.se](http://vsbyggskruv.se)

## ADDRESS

Västsvensk Byggskruv AB  
Vävlagargatan 7  
507 30 Brämhult  
Sweden

