



**Function:** Solid plug with good temperature and ageing properties. The plug design prevents any rotation when installing and allows for targeted anchoring. The plug can be used with most building materials, but is best suited in solid materials such as concrete, stone and solid tile.



**Material:** Nylon.

**Installation instructions:** Drill a hole adapted to suit the size of the plug as shown in the table below. Push the plug into the hole. Fit the fastener with screw adapted to the plug as shown in the same table. The length of the screw should be about 5 mm longer than the plug and attachment together.



D	L	Drill mm	Screw dim. mm	Art.no	Quantity	Pack.	MB
4	20	4	2,5-3,5	334020	100	Packaging	40
4	20	4	2,5-3,5	SB334020	30	Pack	10
5	25	5	3,0-4,0	335025	100	Packaging	40
5	25	5	3,0-4,0	SB335025	25	Pack	10
6	30	6	4,0-5,0	336030	100	Packaging	16
6	30	6	4,0-5,0	SB336030	20	Pack	10
8	40	8	5,0-6,0	338040	100	Packaging	12
8	40	8	5,0-6,0	SB338040	15	Pack	10
10	50	10	6,0-8,0	331050	50	Packaging	12
10	50	10	6,0-8,0	SB331050	10	Pack	10
12	60	12	8,0-10,0	331260	25	Packaging	12
12	60	12	8,0-10,0	SB331260	5	Pack	10
14	70	14	10,0-12,0	331470	20	Packaging	12
14	70	14	10,0-12,0	SB331470	3	Pack	10
16	80	16	12,0-14,0	331680	10	Packaging	12
16	80	16	12,0-14,0	SB331680	2	Pack	10

NOTE: Packs are only sold in multiples of ten.



Produkten bedömd i  
SundaHus Miljödata

