

Product datasheet

Nylon plug LEX



Function: Solid plug with good temperature and ageing properties. The plug design prevents any rotation when installing and allows for targeted anchoring. The plug has a long anchoring section adapted to suit porous materials such as lightweight concrete, lightweight tiles and hollow block.

Material: Nylon.

Installation instructions: Drill a hole adapted to the size of the plug as shown in the table below. Push the plug into the hole. Fit the fastener with screw adapted to the plug as shown in the same table. The length of the screw should be about 5 mm longer than the plug and attachment together.



| D | L | Drill mm | Screw dim. mm | Art.no | Quantity | Pack. | MB |
|---|----|----------|---------------|----------|----------|-----------|----|
| 8 | 80 | 8 | 5,0-6,0 | 368080 | 50 | Packaging | 12 |
| 8 | 80 | 8 | 5,0-6,0 | SB368080 | 6 | Pack | 10 |

NOTE: Packs are only sold in multiples of ten.



Produkten bedömd i
SundaHus Miljödata



CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden

