

# Product datasheet

Nylon plug LE

# V/S/B



**Function:** Solid plug with good temperature and ageing properties. The plug design prevents any rotation when installing and allows for targeted anchoring. The plug has a long anchoring section adapted to suit porous materials such as lightweight concrete, lightweight tiles and hollow block.

**V/S/B**  
VÄSTSVENSK BYGGSKRUV AB

**Material:** Nylon.

**Installation instructions:** Drill a hole adapted to suit the size of the plug as shown in the table below. Push the plug into the hole until the collar is firmly flush to the fastener. Now screw in the screw adapted to suit the plug as shown in the same table. The length of the screw should be about 5 mm longer than the plug and attachment together.

D	L	Max comp. thick. app. mm	Drill mm	Screw dim. mm	Art.no	Quantity	Pack.	MB
10	100	20	10	6,0-8,0	3310100	25	Packaging	12
10	100	20	10	6,0-8,0	SB3310100	3	Pack	10

NOTE: Packs are only sold in multiples of ten.



Produkten bedömd i  
SundaHus Miljödata



## CUSTOMER SERVICE

Tel. 033-23 03 03  
Email: vsb@vsbyggskruv.se  
Website: vsbyggskruv.se

## ADDRESS

Västsvensk Byggskruv AB  
Vävlagargatan 7  
507 30 Bråmhult  
Sweden

