Product datasheet

Nail plug countersunk

Produkten bedömd i SundaHus Miljödata

Function: The nail plug has a solid nylon plug with pre-assembled nail. The nail is cam-threaded and has a bit head. It is therefore very easy to disassemble after installation. The nail plug is designed for use in solid materials such as concrete, stone and solid tile.

Track type bit: Pozidrive 2 and 3.

Material: Plug of nylon and nail of steel.

Coating: Zinc-plated 5 my, for indoor use.

Installation instructions: Drill a hole adapted to suit the size of the nail plug as shown in the table below. Now push the nail plug into the hole until the collar is firmly flush to the fastener. Now knock in the nail with a hammer.

D	L	Bits/Socket	Max comp. thick. app. mm	Drill mm	Art.no	Quantity	Pack.	MB
5	40	2	20		335240	100	Packaging	12
5	40	2	20		SB335240	6	Pack	10
5	50	2	30		335250	100	Packaging	12
5	50	2	30		SB335250	6	Pack	10
6	50	2	25		336050	100	Packaging	12
6	50	2	25		SB336050	6	Pack	10
6	60	2	35		336060	100	Packaging	12
6	60	2	35		SB336060	5	Pack	10
6	80	2	55		336080	100	Packaging	12
6	80	2	55		SB336080	5	Pack	10
6	100	2	75		3360100	100	Packaging	8
6	100	2	75		SB3360100	4	Pack	10
8	60	3	20		338060	50	Packaging	12
8	60	3	20		SB338060	4	Pack	10
8	80	3	40		338080	50	Packaging	8
8	80	3	40		SB338080	4	Pack	10
8	100	3	60		3380100	50	Packaging	8
8	100	3	60		SB3380100	3	Pack	10

NOTE: Packs are only sold in multiples of ten.

CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden

D	L	Bits/Socket	Max comp. thick. app. mm	Drill mm	Art.no	Quantity	Pack.	MB
8	120	3	80		3380120	50	Packaging	8
8	120	3	80		SB3380120	3	Pack	10
8	140	3	100		3380140	50	Packaging	12
8	140	3	100		SB3380140	2	Pack	10

NOTE: Packs are only sold in multiples of ten.

CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden