

Product datasheet

Nail plug collar

V/S/B



Function: The nail plug has a solid nylon plug with pre-assembled nail. The nail is cam-threaded and has a bit head. It is therefore very easy to disassemble after installation. The nail plug is designed for use in solid materials such as concrete, stone and solid tile.

V/S/B

VÄSTSVENSK BYGGSKRUV AB

Track type bit: Pozidrive 2.

Material: Plug of nylon and nail of steel.

Coating: Zinc-plated 5 my, for indoor use.

Installation instructions: Drill a hole adapted to the size of the nail plug as shown in the table below. Now push the nail plug into the hole until the collar is firmly flush to the fastener. Now knock in the nail with a hammer.



D	L	Bits/Socket	Max comp. thick. app. mm	Drill mm	Art.no	Quantity	Pack.	MB
5	30	2	10	5	335030	100	Packaging	16
5	30	2	10	5	SB335030	7	Pack	10
5	40	2	20	5	335140	100	Packaging	12
5	40	2	20	5	SB335140	6	Pack	10
5	50	2	30	5	335050	100	Packaging	12
5	50	2	30	5	SB335050	6	Pack	10
6	40	2	15	6	336140	100	Packaging	12
6	40	2	15	6	SB336140	7	Pack	10

NOTE: Packs are only sold in multiples of ten.



Produkten bedömd i
SundaHus Miljödata



CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Bråmhult
Sweden

