



Function: The coloured nail plug is designed for fitting strips, bases and suchlike in solid materials such as concrete, stone and solid tile. The nail is therefore lacquered/surface treated for colour coordination.



Track type bit: Pozidrive 2.

Material: Plug of nylon and nail of steel.

Coating: ZPY = Zinc-plated 5 my yellow, WHITE = White lacquered RAL 9010, for indoor use.

Installation instructions: Drill a hole adapted to suit the size of the nail plug as shown in the table below. Now push the nail plug into the hole until the collar is firmly flush to the fastener. Now knock in the nail with a hammer.



D	L	Surface treat.	Max comp. thick. app. mm	Drill mm	Art.no	Quantity	Pack.	MB
5	40	WHITE	20	5	345140	100	Packaging	12
5	40	WHITE	20	5	SB345140	6	Pack	10
5	40	ZPY	20	5	345040	100	Packaging	12
5	40	ZPY	20	5	SB345040	6	Pack	10
5	50	WHITE	30	5	345150	100	Packaging	12
5	50	WHITE	30	5	SB345150	5	Pack	10
5	50	ZPY	30	5	345050	100	Packaging	12
5	50	ZPY	30	5	SB345050	5	Pack	10
5	60	WHITE	40	5	345160	100	Packaging	12
5	60	WHITE	40	5	SB345160	5	Pack	10
5	60	ZPY	40	5	345060	100	Packaging	12
5	60	ZPY	40	5	SB345060	5	Pack	10

NOTE: Packs are only sold in multiples of ten.



Produkten bedömd i SundaHus Miljödata

