



Function: Solid nylon plug with good temperature and ageing properties. The façade plug design prevents any rotation when installing and allows for targeted anchoring.




Track type bit: TX 25 and 40.

Material: Plug of nylon and screw of steel.

Coating: Zinc-plated 5 my, for indoor use.

Installation instructions: Drill a hole adapted to the size of the façade plug as shown in the table below. Now push the façade plug into the hole until the collar is firmly flush to the fastener. Now screw the screw into the façade plug.



| D | L | Bits/Socket | Max comp. thick. app. mm | Drill mm | Art.no | Quantity | Pack. | MB |
|----|-----|-------------|--------------------------|----------|-----------|----------|-----------|----|
| 8 | 100 | 25 | 20 | 8 | 3680100 | 50 | Packaging | 8 |
| 8 | 100 | 25 | 20 | 8 | SB3680100 | 4 | Pack | 10 |
| 10 | 100 | 40 | 20 | 10 | 3610100 | 25 | Packaging | 8 |
| 10 | 100 | 40 | 20 | 10 | SB3610100 | 3 | Pack | 10 |
| 10 | 120 | 40 | 40 | 10 | 3610120 | 25 | Packaging | 8 |
| 10 | 120 | 40 | 40 | 10 | SB3610120 | 3 | Pack | 10 |
| 10 | 160 | 40 | 80 | 10 | 3610160 | 25 | Packaging | 12 |
| 10 | 160 | 40 | 80 | 10 | SB3610160 | 2 | Pack | 10 |
| 10 | 180 | 40 | 100 | 10 | 3610180 | 25 | Packaging | 12 |
| 10 | 180 | 40 | 100 | 10 | SB3610180 | 1 | Pack | 10 |

NOTE: Packs are only sold in multiples of ten.



Produkten bedömd i
SundaHus Miljödata

