



Function: Solid nylon plug with good temperature and ageing properties. The façade plug design prevents any rotation when installing and allows for targeted anchoring.



Track type bit: TX 25 and 40.

Material: Plug of nylon and screw of steel.

Coating: Zinc-plated 5 my, for indoor use.

Installation instructions: Drill a hole adapted to the size of the façade plug as shown in the table below. Now push the façade plug into the hole until the collar is firmly flush to the fastener. Now screw the screw into the façade plug.



D	L	Bits/Socket	Max comp. thick. app. mm	Drill mm	Art.no	Quantity	Pack.	MB
8	100	25	20	8	3680100	50	Packaging	8
8	100	25	20	8	SB3680100	4	Pack	10
10	100	40	20	10	3610100	25	Packaging	8
10	100	40	20	10	SB3610100	3	Pack	10
10	120	40	40	10	3610120	25	Packaging	8
10	120	40	40	10	SB3610120	3	Pack	10
10	160	40	80	10	3610160	25	Packaging	12
10	160	40	80	10	SB3610160	2	Pack	10
10	180	40	100	10	3610180	25	Packaging	12
10	180	40	100	10	SB3610180	1	Pack	10

NOTE: Packs are only sold in multiples of ten.



Produkten bedömd i SundaHus Miljödata

