

Product datasheet

Façade plug universal (external)



Function: Solid nylon plug with good temperature and ageing properties. The façade plug has a four-sided anchoring section and is designed to be used with most building materials such as concrete, lightweight concrete, hollow block etc.

Track type bit: TX 40.

Material: Plug of nylon and screw of steel.

Coating: Zincotech Ag, corrosivity class C4, for outdoor use.

Installation instructions: Drill a hole adapted to the size of the façade plug as shown in the table below. Now push the façade plug into the hole until the collar is firmly flush to the fastener. Now screw the screw into the façade plug.



D	L	Max comp. thick. app. mm	Drill mm	Art.no	Quantity	Pack.	MB
10	80	20	10	391080	25	Packaging	8
10	80	20	10	SB391080	4	Pack	10
10	100	40	10	3910100	25	Packaging	8
10	100	40	10	SB3910100	3	Pack	10
10	120	60	10	3910120	25	Packaging	8
10	120	60	10	SB3910120	3	Pack	10
10	140	80	10	3910140	25	Packaging	8
10	140	80	10	SB3910140	2	Pack	10
10	160	100	10	3910160	25	Packaging	12
10	160	100	10	SB3910160	2	Pack	10
10	180	120	10	3910180	25	Packaging	12
10	180	120	10	SB3910180	1	Pack	10

NOTE: Packs are only sold in multiples of ten.



Produkten bedömd i
SundaHus Miljödata



CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden

