


Function: Robust metal attachment for heavy installation in porous materials such as lightweight concrete and tiles. The attachment has a square profile that prevents rotation in porous material.

Material: Steel.

Coating: Zinc-plated 5 my, for indoor use.

Installation instructions: Drill a hole adapted to suit the size of the anchor as shown in the table below. In very porous material, the smaller hole is drilled according to the table, and for larger material a larger hole is drilled. Now fit the lightweight concrete anchor by knocking it into the hole using a hammer. The fastening is then fitted with the screw that is adapted to suit the anchor as shown in the table below. The length of the screw should be about 5 mm longer than the anchor and attachment together.



Produkten bedömd i
SundaHus Miljödata



D	L	Min. drill depth mm	Drill mm	Screw dim. mm	Art.no	Quantity	Pack.	MB
6	32	40	5-6	5,0-6,0	376032	200	Packaging	12
6	32	40	5-6	5,0-6,0	SB376032	8	Pack	10
8	60	70	6-8	6,0-8,0	378060	50	Packaging	12
8	60	70	6-8	6,0-8,0	SB378060	5	Pack	10
10	60	70	8-10	8,0-10,0	371060	50	Packaging	12
10	60	70	8-10	8,0-10,0	SB371060	4	Pack	10

NOTE: Packs are only sold in multiples of ten.

