



Function: The express nail is a metal attachment for use in solid materials such as concrete and stone. When the express nail is inserted into a pre-drilled hole, the nail is pressed together, springs out and expands along the entire nail.

Material: Hardened spring steel.

Coating: Zinc-plated 5 my, for indoor use.

Installation instructions: Drill a hole adapted to suit the size of the express nail as shown in the table below. Now knock in the express nail using a hammer until the collar is flush to the fastener.



D	L	Min. drill depth mm	Max comp. thick. app. mm	Drill mm	Art.no	E-number	Quantity	Pack.	MB
6	30	25	5	6	B376030		8000	Bulk pack	
6	30	25	5	6	376030		200	Packaging	12
6	60	30	30	6	B376060		3500	Bulk pack	
6	60	30	30	6	376060		100	Packaging	12
6	60	30	30	6	SB376060		7	Pack	10
6	80	30	50	6	B376080		2000	Bulk pack	
6	80	30	50	6	376080		100	Packaging	12
6	100	30	70	6	B3760100		1500	Bulk pack	
6	100	30	70	6	3760100		100	Packaging	8
8	70	40	30	8	B378070		2000	Bulk pack	
8	70	40	30	8	378070		100	Packaging	8
8	70	40	30	8	SB378070		6	Pack	10
8	90	40	50	8	B378090		1500	Bulk pack	
8	90	40	50	8	378090		100	Packaging	12
8	90	40	50	8	SB378090		5	Pack	10
8	110	40	70	8	B3780110		1000	Bulk pack	
8	110	40	70	8	3780110		100	Packaging	12
8	110	40	70	8	SB3780110		4	Pack	10

NOTE: Packs are only sold in multiples of ten.



Product datasheet

Express nail



D	L	Min. drill depth mm	Max comp. thick. app. mm	Drill mm	Art.no	E-number	Quantity	Pack.	MB
8	130	40	90	8	B3780130		700	Bulk pack	
8	130	40	90	8	37801309		50	Packaging	8
8	150	40	110	8	B3780150		500	Bulk pack	
8	150	40	110	8	37801509		50	Packaging	12

NOTE: Packs are only sold in multiples of ten.

CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden

