



**Function:** Frame socket classified to Swedish standard SS 817332:2021 for wood frame bracket. Can also be used for attaching frames to concrete, light concrete, hollow block or beam max 6 mm. The socket is screwed into a pre-drilled hole in the frame. The frame can be adjusted by turning the socket with the adjuster key. The socket is locked in place using a custom screw designed to suit the surface.



**Material:** Zinc.

**Installation instructions:** The socket is screwed into a 14 mm pre-drilled hole from the outside/wall side of the frame. Frame alignment is set both vertically and horizontally. Now unscrew the socket to the base and adjust the frame using the adjusting key. Make sure that at least 15 mm of the length of the sleeve is anchored in the frame. Lock the socket in place using a screw designed for the surface from our range. Cover the holes with frame anchor covers.



	D	L	Art.no	E-number	Quantity	Pack.	MB
*	16	28	B44228		1000	Bulk pack	
*	16	28	4422899		50	Packaging	8
*	16	28	44328		25	Packaging	12
*	16	28	SB44228		6	Pack	10
*	16	28	SB442289		4	Pack	10
	16	40	B44240		900	Bulk pack	
	16	40	442409		40	Packaging	8
	16	40	44340		25	Packaging	12
	16	40	SB44240		6	Pack	10
	16	40	SB442409		4	Pack	10
	16	60	B44260		600	Bulk pack	
	16	60	44360		16	Packaging	12
	16	60	SB44260		6	Pack	10
	16	60	SB442609		4	Pack	10

\*Classification according to SS 817332 does not apply to this dimension. NOTE: Packs are only sold in multiples of ten.

