



Function: Unhardened frame screw for frame attachment for installing in wood, concrete, lightweight concrete etc. The screw has a fixed adjuster sleeve that is screwed into a pre-drilled hole. The frame can be adjusted by turning the sleeve with the adjuster key. For installation in concrete, lightweight concrete, etc., a suitable nylon plug is used.

Material: Screw of unhardened steel and sleeve in zinc.

Coating: Zinc-plated 5 my, for indoor use.

Installation instructions: Frame is set both vertically and horizontally Pre-drill a 14 mm hole with a drill bit in the frame and 5 mm (centre drill) in the surface. Place the frame screw on the installation tool and screw the sleeve about 10 mm below the frame surface. Remove any wedges on the frame sides and adjust the frame with the installation tool. Cover the holes with frame anchor covers.



Produkten bedömd i
SundaHus Miljödata



D	L	Art.no	E-number	Quantity	Pack.	MB
7	50	B44050		1000	Bulk pack	
7	50	440509		70	Packaging	8
7	50	44150		25	Packaging	12
7	50	SB44050		6	Pack	10
7	50	SB440509		4	Pack	10
7	70	B44070		900	Bulk pack	
7	70	4407099		50	Packaging	8
7	70	44170		25	Packaging	12
7	70	SB44070		6	Pack	10
7	70	SB44067		4	Pack	10
7	90	B44090		600	Bulk pack	
7	90	440909		50	Packaging	8
7	90	44190		20	Packaging	12
7	90	SB44099		6	Pack	10
7	90	SB44097		4	Pack	10
7	140	B44120		400	Bulk pack	
7	140	441209		40	Packaging	8
7	140	SB441209		4	Pack	10

NOTE: Packs are only sold in multiples of ten.

CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden



Product datasheet

Frame screw unhardened



D	L	Art.no	E-number	Quantity	Pack.	MB
7	140	SB44120		3	Pack	10

NOTE: Packs are only sold in multiples of ten.

CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden

