

Product datasheet

Frame socket screw with plug

V/S/B



Function: The screw together with the plug is meant to be used to fix frame sockets when installing into aerated concrete, lightweight clinker, hollow stone, and concrete.

Track type bit: TX 40.

Material: Plug made of nylon and screw made of steel.

Coating: Electro-galvanized 5 my, for indoor use.

Installation instructions: After the frame socket is installed and the frame is adjusted to the correct position, fix the frame socket with the frame socket screw together with the plug. Drill a hole in the surface through the frame socket when the window/door is in place. Attach the screw to the plug, then tap the plug through the frame socket until the collar reaches the bottom of the frame socket. Then screw in the screw into the plug.

V/S/B

VÄSTSVENSK BYGGSKRUV AB

D	Drill mm.	L	Art.no	Quantity	Pack	MB
8		100	4480100	25	8	
8		100	SB4480100	4	10	
8		120	4480120	25	8	
8		120	SB4480120	4	10	

NOTE: Packs are only sold in multiples of ten.



Produkten bedömd i
SundaHus Miljödata



CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Bråmhult
Sweden

