



Function: Thonic tc-id is an inspection hatch for recessed and visually restricted assembly. The hatch is screwed in place with a drywall screw into the rear flange, the joints and screw holes are then rendered. The hatch must be fitted before painting. The hatch comes in standard sizes from 150 x 150 to 600 x 600 mm and in versions for single and double drywall boards. Thonic tc-id is delivered unpainted. For sizes up to 300 x 300 mm, the hatch has a self-fixing lock. For sizes larger than 300 x 300 mm, the hatch is fitted with a countersunk drive lock. When installing on ceilings, we recommend that the hatch be fitted with a hinged tc-gj and drive lock tc-ml. Thonic tc-ue can be ordered to size with alternative sizes, in any colour or with optional accessories such as a range of hinges, lock models, etc.



Hole making measurements	Design	Frame external dimensions	Light dimensions	Locking	Art.no	Quantity
150 x 150	1-layer drywall	190 x 190	113 x 113	Snap lock	4115	1
200 x 200	1-layer drywall	240 x 240	163 x 163	Snap lock	4120	1
300 x 300	1-layer drywall	340 x 340	263 x 263	Snap lock	4130	1
400 x 400	1-layer drywall	440 x 440	363 x 363	Driver lock	4140	1
500 x 500	1-layer drywall	540 x 540	463 x 463	Driver lock	4150	1
600 x 600	1-layer drywall	640 x 640	563 x 563	Driver lock	4160	1
150 x 150	2-layer drywall	190 x 190	113 x 113	Snap lock	4215	1
200 x 200	2-layer drywall	240 x 240	163 x 163	Snap lock	4220	1
300 x 300	2-layer drywall	340 x 340	263 x 263	Snap lock	4231	1
400 x 400	2-layer drywall	440 x 440	363 x 363	Driver lock	4240	1
500 x 500	2-layer drywall	540 x 540	463 x 463	Driver lock	4250	1
600 x 600	2-layer drywall	640 x 640	563 x 563	Driver lock	4260	1



Produkten bedömd i
SundaHus Miljödata



CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Bråmhult
Sweden

