



Function: Thonic tc-bd is a fire rated type approved inspection hatch fitted with a surface mounted frame. Installation is very quick as the fastening plates are pre-assembled and knocked out with a hammer between the first and second drywall boards. The hatch comes in standard size from 150 x 150 to 600 x 600 mm. Thonic tc-bd is delivered white painted, NCS S 0502-Y. The hatch is fitted with a countersunk drive lock. Thonic tc-ue can be customised with other sizes, in any colour or with optional accessories such as a range of hinges, lock models, etc. The type approvals in question are no. 0118/04 (EI30) and no. 0117/04 (EI60).

Hole making measurements	Design	Frame external dimensions	Light dimensions	Number of fixing pads	Locking	Art.no	Quantity
150 x 150	EI30	190 x 190	113 x 113	4	Driver lock	3015	1
200 x 200	EI30	240 x 240	163 x 163	4	Driver lock	3020	1
300 x 300	EI30	340 x 340	263 x 263	8	Driver lock	3030	1
400 x 400	EI30	440 x 440	363 x 363	8	Driver lock	3040	1
500 x 500	EI30	540 x 540	463 x 463	8	Driver lock	3050	1
600 x 600	EI30	640 x 640	563 x 563	12	Driver lock	3060	1
150 x 150	EI60	190 x 190	113 x 113	4	Driver lock	6015	1
200 x 200	EI60	240 x 240	163 x 163	4	Driver lock	6020	1
300 x 300	EI60	340 x 340	263 x 263	8	Driver lock	6030	1
400 x 400	EI60	440 x 440	363 x 363	8	Driver lock	6040	1
500 x 500	EI60	540 x 540	463 x 463	8	Driver lock	6050	1
600 x 600	EI60	640 x 640	563 x 563	12	Driver lock	6060	1

