



Function: Thonic tc-vm is an inspection hatch for wet rooms fitted with a surface mounted frame. Installation is very quick as the fastening plates are pre-assembled and knocked out with a hammer behind the first drywall board or between the drywall boards when installed in double drywall. The hatch comes in standard size from 150 x 150 to 400 x 400 mm. Thonic tc-vm is delivered white painted, NCS S 0502-Y. The hatch is fitted with a countersunk drive lock. When installing in roofs, we recommend that the hatch is fitted with a wire guard tc-vs. Thonic tc-vm can be customised with other sizes, in any colour or with optional accessories such as wire guard, a range of lock models, etc.



Hole making measurements	Frame external dimensions	Light dimensions	Number of fixing pads	Locking	Art.no	Quantity
150 x 150	190 x 190	113 x 113	4	Driver lock	4615	1
200 x 200	240 x 240	163 x 163	4	Driver lock	4620	1
300 x 300	340 x 340	263 x 263	4	Driver lock	4630	1
400 x 400	440 x 440	363 x 363	8	Driver lock	4640	1



Produkten bedömd i
SundaHus Miljödata



CUSTOMER SERVICE

Tel. 033-23 03 03
Email: vsb@vsbyggskruv.se
Website: vsbyggskruv.se

ADDRESS

Västsvensk Byggskruv AB
Vävlagargatan 7
507 30 Brämhult
Sweden

