Declaration of performance

Hardwood screw (A4 stainless) for wood stud



15000



Applications: Decking screw for wood constructions in pressure impregnated wood and hardwood.



Manufacturer:

Västsvensk Byggskruv AB Vävlagargatan 7, SE-507 30 Brämhult +46 33-23 03 03 vsbyggskruv.se

Type testing: RISE (Research Institutes of Sweden AB) NB 0402, has performed initial type testing, according to the harmonized standard SS-EN14592: 2008+A1:2012; Wood constructions - Dowel-type fasteners made of steel. System of assessment and continuous monitoring of performance: System 3.

PERFORMANCE

ESSENTIAL CAPACITY	PERFORMANCE	REPORT
Characteristic yield moment M _{y,k} (Nmm)	3 760	SP 5P09658B Rev 1 2016.04.21
Characteristic withdrawal parameter f _{ax,k} (N/mm²) in wood with characteristic density 350 Kg/m³	12,8	SP 5P09658B Rev 1 2016.04.21
Characteristic head pull-through parameter $f_{head,k}$ (N/mm²) in wood with characteristic density 350 Kg/m³	29,6	SP 5P09658B Rev 1 2016.04.21
Characteristic tensile capacity f _{tens,k} (kN)	6,9	SP 5P09658C 2016.05.31 RISE 2P03958 2020.04.29
Characteristic torsional ratio $f_{tor,k}/R_{tor,k}$ in wood with characteristic density 350 Kg/m ³	3,4	SP 5P09658B Rev 1 2016.04.21
DURABILITY	Climate class 3 (according to EN 1995-1-1)	

The performance of the product above is consistent with the specified performance. The declaration of performance has been issued in accordance with regulation (Eu) no. 305/2011 at the sole responsibility of the manufacturer specified above.

Brämhult 2021.11.04

Lars Helgesson Quality manager

Declaration of performance

Hardwood screw (A4 stainless) for wood stud



15000

All measurements in mm

Item number	Name	Head diameter	Thread length	Inner diameter thread
75560	Hardwood screw Wood Jetting 5,5 x 60 A4	6,90	27,00	3,80
B75560	Hardwood screw Wood Jetting 5,5 x 60 A4	6,90	27,00	3,80
P75560	Hardwood screw Wood Jetting 5,5 x 60 A4	6,90	27,00	3,80