


Declaration of performance

Collated chipboard screw cutting for wood stud



Applications: Chipboard screw for boards and wood constructions.

Manufacturer:
Västsvensk Byggskruv AB
Vävlagargatan 7, SE-507 30 Brämhult
+46 33-23 03 03
vsbyggskruv.se



Type testing: RISE (Research Institutes of Sweden AB) NB 0402, has performed initial type testing, according to the harmonized standard SS-EN14592: 2008+A1:2012; Wood constructions - Dowel-type fasteners made of steel. System of assessment and continuous monitoring of performance: System 3.

PERFORMANCE

ESSENTIAL CAPACITY	PERFORMANCE	REPORT
Characteristic yield moment $M_{y,k}$ (Nmm)	4 260	SP 4P05324 2014.12.02
Characteristic withdrawal parameter $f_{ax,k}$ (N/mm ²) in wood with characteristic density 350 Kg/m ³	11,3	SP 6P10228 2017.01.24
Characteristic head pull-through parameter $f_{head,k}$ (N/mm ²) in wood with characteristic density 350 Kg/m ³	33,9	SP 6P10228 2017.01.24
Characteristic tensile capacity $f_{tens,k}$ (kN)	6,6	SP 4P05324 2014.12.02 RISE 2P03958 2020.04.29
Characteristic torsional ratio $f_{tor,k}/R_{tor,k}$ in wood with characteristic density 350 Kg/m ³	2,5	SP 4P05324 2014.12.02

DURABILITY

Climate class 1
(according to
EN 1995-1-1)

The performance of the product above is consistent with the specified performance. The declaration of performance has been issued in accordance with regulation (Eu) no. 305/2011 at the sole responsibility of the manufacturer specified above.

Brämhult 2021.11.05

Lars Helgesson
Quality manager

Declaration of performance

Collated chipboard screw cutting for wood stud

All measurements in mm

Specifications Collated chipboard screw cutting for wood stud

Item number	Name	Head diameter	Thread length	Inner diameter thread
RBC8030	Chipboard screw Wood Cut. 4,2 x 30 ZP Collated	7,00	21,00	2,50
RBC8041	Chipboard screw Wood Cut. 4,2 x 41 ZP Collated	7,00	21,00	2,50
RBC8055	Chipboard screw Wood Cut. 4,2 x 55 ZP Collated	7,00	33,00	2,50